

SEALED BID

Do Not Return Via Email or Fax

Mailing Address:
P. O. Box 1948
Mobile, Alabama 36633
(251) 208-7434

CITY OF MOBILE

**Purchasing Department
and Package Delivery:
Bid Delivery Address:**

**Government Plaza
4th Floor, Room S-408
205 Government St.
Mobile, Alabama 36644**

Postal Service Does Not Deliver to This Street Address

BID SHEET

This is Not an Order

**READ TERMS AND CONDITIONS
ON REVERSE SIDE OF THIS PAGE
BEFORE BIDDING**

Typed by: lw

Buyer: 005

Please quote the lowest price at which you will furnish the articles listed below

DATE	BID NO.	DEPARTMENT	Commodities to be delivered F.O.B. Mobile to:
8/13/2026	6064	TRAFFIC ENGINEERING	TO BE SPECIFIED

This bid must be received and stamped by the Purchasing office not later than:

11:30 A.M., TUESDAY, SEPTEMBER 1, 2026

QUANTITY	ARTICLES	UNIT	UNIT PRICE		EXTENSION	
			Dollars	Cents	Dollars	Cents
	STREET LIGHTING POLES/ARMS/PED POLES					
Appx 1-5	Pole, Traffic Signal 37' steel dual mast arms (65' & 50') with 12' Luminaire Extension and MUST MEET ATTACHED SPECIFICATIONS Make_____Model_____					
Appx 1-5	Pole, Traffic Signal 20' steel, mast arms (45 & 50') with 12' luminaire extension,MUST MEET ATTACHED SPECIFICATIONS Make_____Model_____					
Appx 1-5	Pole, Traffic Signal Pedestrian poles 10' steel for PP-1, 2, 3 & 4 MUST MEET ATTACHED SPECIFICATIONS Make_____Model_____					
TO BE AWARDED ON AN ALL OR NONE BASIS.						
ALL POLES MUST MEET THE ATTACHED SPECIFICATIONS AND MATCH WHAT IS CURRENTLY IN PLACE. PLEASE SEE THE PICTURES THAT ARE ATTACHED WITH THIS BID.						
BIDDER WILL BE REQUIRED TO SUBMIT SPEC SHEETS WITH THE RETURN BID.						
QUOTE DELIVERED PRICING FOB MOBILE.						
PRICING SHALL BE FIRM FOR A ONE (1) YEAR PERIOD FOLLOWING THE AWARD OF THIS BID.						
Page 1 of 3			TOTAL			

**RETURN ONE SIGNED COPY OF THIS BID
IN ENCLOSED ENVELOPE**

State delivery time within _____ days of receipt of P.O.

Phone Number _____

Firm Name _____

Email Address _____

Signature _____

Type or Print Name _____

1. All quotations must be signed with the firm name and by an authorized officer or employee.
2. Verify your bid before submission as it cannot be changed or corrected after being opened. In case of error in extension of prices, the unit price will govern.
3. If you do not bid, return this sheet and state reason. Otherwise, your name may be removed from our mailing list.
4. The right is reserved to reject any, or all quotations, or any portions thereof, and to waive technicalities if deemed to be in the interest of the City of Mobile.
5. This bid shall not be reassignable except by written approval of the Purchasing Agent of the City of Mobile.
6. State brand and model number of each item. All items bid must be new and latest model unless otherwise specified.
7. If bid results are desired, enclose a self-addressed and stamped envelope with your bid. (All or None bids only)
8. Do not include Federal Excise Tax as an exemption certificate will be issued in lieu of same. The City is exempt from the State of Alabama and City sales taxes.
9. PRICES ARE TO BE FIRM AND F.O.B. DESTINATION UNLESS OTHERWISE REQUESTED.
10. BID WILL BE AWARDED ON ALL OR NONE BASIS UNLESS OTHERWISE STATED.
11. Bids received after specified time will be returned un-opened.
12. Failure to observe stated instructions and conditions will constitute grounds for rejection of your bid.
13. Furnish literature, specifications, drawings, photographs, etc., as applicable with the items bid.
14. Vendor may be required to obtain City of Mobile Business License as applicable to City of Mobile Municipal Code Section 34-50. For Business License inquiry, contact the Revenue Department at (251) 208-7462 or cityofmobile.org/business-license-overview/
15. IF a bid bond is required in the published specifications, see below:
 Each bid shall be accompanied by a **Cashier's Check, Certified Check, Bank Draft or Bid Bond** for the sum of five (5) Percent of the amount bid, made payable to the City of Mobile and certified by a reputable banking institution. All checks shall be returned promptly, except the check of the successful bidder, which shall be returned after fulfilling the bid.
16. Contracts in excess of \$50,000 require that the successful bidder make every possible effort to have at least fifteen (15) percent of the total value of the contract performed by socially and economically disadvantaged individuals.
17. All bids/bid envelopes must have the bid number noted on the front. Bids that arrive unmarked and are opened in error shall be returned to vendor as an unacceptable bid.
18. If successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Alabama Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for and issuance of a Certificate of Authority may be several weeks.
19. Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State to submit a bid, but may need to obtain the Business License and Certificate of Authority if applicable, prior to issuance of a Purchase Order.
20. Bids and addendums are posted at www.cityofmobile.org/services/business/bids/. It is the responsibility of the vendor to check the City's bid page for updates and addendums.
21. Vendors must be able to provide the following upon request. Federal W-9 form, proof of registration in the E-Verify program, and Certificate of Authority to do business in Alabama/Registration with the Alabama Secretary of State within 24 hours of request.
22. City of Mobile applies local vendor preference to all purchases: Code of Alabama, 1975, Sections 41-16-50(a) and 41-16-50(d), except federally funded grants.
23. Equal Employment Opportunity. Except as otherwise provided under 41 CFR part 60, all contracts that meet the definition of "federally assisted construction contract" in 41 CFR Part 60-1.3 must include the equal opportunity clause provided under 41 CFR 60-1.4(b), in accordance with Executive Order 11246, "Equal Employment Opportunity" (30 FR 12319, 12935, 3 CFR Part, 1964-1965 Comp., p. 339), as amended by Executive Order 11375, "Amending Executive Order 11246 Relating to Equal Employment Opportunity," and implementing regulations at 41 CFR part 60, "Office of Federal Contract Compliance Programs, Equal Employment Opportunity, Department of Labor."
24. Davis-Bacon Act, as amended (40 U.S.C. 3141-3148) will apply when required by Federal program regulations.

BID CONTINUATION SHEET

Page _____ of _____

QUANTITY	ARTICLES	UNIT	UNIT PRICE		EXTENSION	
			Dollars	Cents	Dollars	Cents
	Page 2 of 3 SYSTEM / PRODUCTS BID ARE TO BE COMPATIBLE WITH EXISTING EQUIPMENT IN USE BY THE CITY OF MOBILE. CITY WILL ASSIST WITH THE UNLOADING. VENDOR/TRUCK LINE MUST CALL AT LEAST 24 HOURS PRIOR TO DELIVERY ATTEMPT. TRUCK CAN BE MET/ UNLOADED BETWEEN 7:30 A.M. AND 1:00 P.M. ONLY. NOTIFICATION REQUIRED TO ENSURE EQUIPMENT IN PLACE FOR UNLOADING. All vendors will be required to provide verification of enrollment in the E-Verify program. Additional information may be found at http://immigration.alabama.gov/ If the successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See: www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for the issuance of a Certificate of Authority may be several weeks. Upon notification, vendor will have 10 business days to provide the Certificate of Authority and the E-Verify numbers to the Purchasing Department before award can be completed. (Vendors will possibly need to pay the expedite fee to meet this requirement because application is not sufficient. We must have a copy of the certificate with your Company ID number). Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State, nor the E-Verify for certification to submit a bid, but will need to obtain the Business License and Certificate of Authority verification and/or provide the E-Verify Certification, if applicable, prior to issuance of a Purchase Order. If you have not received a Purchase Order from the City of Mobile within the past 6 months, please include your W9 and the completed Vendor form with your bid . These forms are included with your bid package. The contact information should be for your Sales Department. Please include: telephone number, fax number and a valid e-mail address.					
			TOTAL			

**RETURN ONE SIGNED COPY OF THIS QUOTATION
IN ENCLOSED ENVELOPE**

READ ABOVE INSTRUCTIONS BEFORE QUOTING

Firm Name _____

By _____

BID CONTINUATION SHEET

Page _____ of _____

QUANTITY	ARTICLES	UNIT	UNIT PRICE		EXTENSION	
			Dollars	Cents	Dollars	Cents
	Page 2 of 3 SYSTEM / PRODUCTS BID ARE TO BE COMPATIBLE WITH EXISTING EQUIPMENT IN USE BY THE CITY OF MOBILE. CITY WILL ASSIST WITH THE UNLOADING. VENDOR/TRUCK LINE MUST CALL AT LEAST 24 HOURS PRIOR TO DELIVERY ATTEMPT. TRUCK CAN BE MET/ UNLOADED BETWEEN 7:30 A.M. AND 1:00 P.M. ONLY. NOTIFICATION REQUIRED TO ENSURE EQUIPMENT IN PLACE FOR UNLOADING. All vendors will be required to provide verification of enrollment in the E-Verify program. Additional information may be found at http://immigration.alabama.gov/ If the successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See: www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for the issuance of a Certificate of Authority may be several weeks. Upon notification, vendor will have 10 business days to provide the Certificate of Authority and the E-Verify numbers to the Purchasing Department before award can be completed. (Vendors will possibly need to pay the expedite fee to meet this requirement because application is not sufficient. We must have a copy of the certificate with your Company ID number). Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State, nor the E-Verify for certification to submit a bid, but will need to obtain the Business License and Certificate of Authority verification and/or provide the E-Verify Certification, if applicable, prior to issuance of a Purchase Order. If you have not received a Purchase Order from the City of Mobile within the past 6 months, please include your W9 and the completed Vendor form with your bid . These forms are included with your bid package. The contact information should be for your Sales Department. Please include: telephone number, fax number and a valid e-mail address.					
			TOTAL			

**RETURN ONE SIGNED COPY OF THIS QUOTATION
IN ENCLOSED ENVELOPE**

READ ABOVE INSTRUCTIONS BEFORE QUOTING

Firm Name _____

By _____

CITY OF MOBILE

SPECIFICATIONS FOR STEEL TRAFFIC SIGNAL POLES

i. General

- a. The following are the requirements for steel traffic signal poles and pedestrian poles as shown in **Appendix A**. These requirements may be supplemented by the requirements given on the details attached hereto as a part of this specification. The poles will be for City of Mobile Project 2025-3005-20 to widen and construct a traffic signal at the intersection of McGregor Ave. and Springhill Ave.

A traffic signal pole shall consist of a tapered, fluted pole, tapered traffic signal mast arm(s), luminaire arm(s), if required, anchor bolts, base plate, and any other features as described in this specification and attached plans. All visible features of the mast arms, poles, luminaire arm(s), etc. must be coated in **BLACK**.

A pedestrian pole shall consist of a tapered, fluted pole, if required, anchor bolts, base plate, and any other features as described in this specification and attached plans. All visible features of the mast arms, poles, luminaire arm(s), etc. must be coated in **BLACK**.

Please reference Appendix B for an example pole design and drawings this proposal shall match.

ii. Design/Fabrication

- a. All materials used in the fabrication of traffic signal structural supports shall meet the requirements of the AASHTO Standard Specifications for Structural Supports for Highway Signs, Luminaires and Traffic Signals, 2022 edition as per the latest ALDOT Standard Specifications. Calculations and detailed drawings shall be submitted demonstrating compliance with the specifications. They shall include stress analysis on the mast arm, luminaire arm, pole, base plate, and anchor bolts. Maximum loads and stresses shall be determined for the most critical wind direction. The tube's drag coefficients shall be increased to include the effects of fluted shapes.

All grades of steel listed in the AASHTO Standard Specifications for Highway Bridges are applicable for welded structural supports for traffic signals and shall have a specified yield strength not less than 35 ksi.

- b. Steel Poles

The shafts shall be fabricated from basic oxygen or open hearth sheet steel, of a single ply, and having only one longitudinal seam weld. Steel poles shall be anchored with a one piece cast steel anchor base or a welded steel plate anchor base that is of sufficient strength to develop the yield strength of the pole. When the anchor base is attached to the shaft it shall develop the full strength of the shaft section to resist bending action. The base shall be provided with four slotted holes for attachment to the foundation with four anchor bolts. Each pole will have an internal grounding lug inside each pole near the hand hole.

c. Mast Arms

Mast arms shall be curved, smooth upswept round shafts fabricated from steel tubes to the lengths specified on the bid and attached plan set. Mast arms shafts shall be of one continuous piece without intermediate splices or couplings, provided with rain-tight connections to the shaft of the pole and designed to bolt in place as designed. A two piece section, slip joint shaft mast arm will be permitted if this bid requires mast arms longer than the manufacturer's length capability.

d. Luminaire Arms

Luminaire arms shall be curved, smooth upswept round shafts. The luminaire arms shall be manufactured from 2 inch Schedule 40 pipe (2-3/8 inch O.D.) with a scroll brace attachment. The arm shall be design to attach to the shaft of the signal pole with option to rotate three hundred and sixty degrees in the horizontal plane. The luminaire is not a part of this bid. The design of the luminaire arm included in the bid shall be submitted with the bid, in addition to any alternative design that can be substituted at no additional cost.

e. Anchor Bolt Assemblies

Anchor bolt assemblies (anchor bolts, nuts, and washers) shall be in accordance with AASHTO M 314, Grade 36 or Grade 55, except maximum tensile strength on all grades is waived, and capable of transferring the load safely from the structure base plate to the foundation. The exposed end of the anchor bolts shall be threaded (rolled or cut type) and provided with appropriate nuts, including lock nuts and flat washers. The anchor bolts, nuts, and washers shall be hot-dipped galvanized in accordance with AASHTO M 232, however, galvanization of the bolt below 6 inches from the top of the embedment line will not be required. The nuts shall be lubricated with a lubricant containing a visible dye so that a visual check can be made for proper

lubrication prior to installation. Special care shall be taken when storing galvanized bolts with a water soluble lubricant.

f. Finish

All poles, mast arms and attachments shall be hot dipped galvanized per ASTM-A123. Powdered coating or wet coat painting urethane primer/polyurea finish. The finished color shall be gloss black. Material shall be wrapped and protected to prevent damage during shipping, storage and construction.

g. Metal Traffic Signal Pole with Mast Arm Assembly

The Metal Traffic Signal Pole with Mast Arm Assembly shall include furnishing the metal traffic signal pole, mast arm assembly, luminaire arm, and all features and hardware necessary as described in this specification and illustrated in the attached plans within **Appendix A**.

Payment will be made under the following Line Items:

(1) Traffic Signal Pole, 37' Steel, Dual Mast Arms (65' & 50') with 12' Luminaire Extension

- a. Note: FMA-2 (Future Mast Arm 2 = 50 mast arm) needs to be considered for the Pole #1's design but will not be purchased through this bid.

(2) Traffic Signal Pole, 20' Steel, Mast Arms (45' & 50') with 12' Luminaire Extension.

- a. Plans call for the luminaire but it will not be installed. Do not incorporate into the pole's design.

(3) Traffic Signal Pedestrian Poles, 10' Steel for PP-1, 2, 3, & 4 (4 total pedestrian poles). See Appendix A and B for details.

Appendix A

McGregor and Springhill Signal Plan Set

TRAFFIC SIGNAL AND ITS LEGEND

[illegible]

TRAFFIC SIGNAL SUMMARY OF QUANTITIES

LEGEND	
A	T.S.D.-730-1
B	T.S.D.-730-2B
C	T.S.D.-730-4
D	T.S.D.-730-9
E	T.S.D.-730-9A
F	T.S.D.-730-10
G	T.S.D.-730-12
H	T.S.D.-730-13
I	T.S.D.-730-14
J	T.S.D.-730-18



GreshamSmith.com
2222 Arlington Ave. South
Birmingham, AL 35205

205.298.9220

TRAFFIC
SIGNAL
DESIGN AT
MCGREGOR
AVE AND
SPRING HILL
AVE



City of Mobile
85 North
Mobile, Alabama 36604



REQUIRED TRAFFIC SIGNAL PAY ITEMS (LUMP SUM)

LOCATION	REMOVAL OF EXISTING TRAFFIC CONTROL UNIT (NORTH MCGREGOR AVENUE AT SPRING HILL AVENUE)	FURNISHING AND INSTALLING TRAFFIC CONTROL UNIT (NORTH MCGREGOR AVENUE AT SPRING HILL AVENUE)	VIDEO DETECTION SYSTEM (NORTH MCGREGOR AVENUE AT SPRING HILL AVENUE)	FURNISHING AND INSTALLING PEDESTAL POLE AND FOUNDATION WITH PEDESTRIAN SIGNAL FEATURES	FURNISHING AND INSTALLING PEDESTAL POLE AND FOUNDATION WITH PEDESTRIAN SIGNAL FEATURES	FURNISHING AND INSTALLING PEDESTAL POLE AND FOUNDATION WITH PEDESTRIAN SIGNAL FEATURES	FURNISHING AND INSTALLING PEDESTAL POLE AND FOUNDATION WITH PEDESTRIAN SIGNAL FEATURES	FURNISHING AND INSTALLING PEDESTAL POLE AND FOUNDATION WITH PEDESTRIAN SIGNAL FEATURES	FURNISHING AND INSTALLING PEDESTAL POLE AND FOUNDATION WITH PEDESTRIAN SIGNAL FEATURES	STANDARD DWG NO	REMARKS
N. MCGREGOR AVE AT SPRING HILL AVE	730-A	730-C	730-U	730-Y1	730-Y2	730-Y3	730-Y4	730-Y5	730-Y6	C, D, E, G, J	
	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM		
TOTALS	1	1	1	1	1	1	1	1	1		

REQUIRED TRAFFIC SIGNAL EQUIPMENT (EACH PAY ITEMS)

LOCATION	METAL TRAFFIC SIGNAL POLE FOUNDATION (POLIC 1)	METAL TRAFFIC SIGNAL POLE WITH FOUNDATION (POLIC 2)	METAL TRAFFIC SIGNAL POLE WITH 65' MAST ARM ASSEMBLY	METAL TRAFFIC SIGNAL POLE WITH 45' & 50' MAST ARM ASSEMBLIES	WALL MOUNTED JUNCTION BOX TYPE SZ	LUMINAIRE EXTENSION ASSEMBLY, 1.2 FEET	VEHICULAR SIGNAL HEAD, 12 INCH, 3 SECTION, TYPE LED	VEHICULAR SIGNAL HEAD, 12 INCH, 4 SECTION, TYPE LED	PEDESTRIAN SIGNAL HEAD, 12 INCH, TYPE LED	MISCELLANEOUS EQUIPMENT, PEDESTRIAN PUSH BUTTON	CONTROLLER ASSEMBLY, TYPE REMA, 16 CHANNELS	ELECTRICAL POWER SERVICE ASSEMBLY WITH WOOD POLE	REMARKS
N. MCGREGOR AVE AT SPRING HILL AVE	730-E1	730-E2	730-F1	730-G2	730-K	730-N	730-P1	730-P2	730-P3	730-Q	730-R	730-I	B, C, D, F, H
	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	EACH	
TOTALS	1	1	1	1	1	1	1	1	1	1	1	1	

NOTE: THE CITY OF MOBILE IS PURCHASING THE POLES AND MAST ARMS FOR THIS PROJECT


NOT TO SCALE

TRAFFIC SIGNAL
SUMMARY OF
QUANTITIES

SHEET NO.	48
TOTAL SHEETS	64

100% PLAN SUBMITTAL

SCHEMATIC WIRING DIAGRAM



FOUNDATIONS TO BE PROVIDED BY CONTRACTOR PER PLAN.

TSD-730-18

NON-METALLIC CONDUIT
DIRECTIONAL BORE

100% PLAN SUBMITTAL

VIDEO DETECTION SPECIAL DETAILS


REFERENCE PROJECT NO	FISCAL YEAR	SHEET NO
2025-3005-20	2026	50A



NOTES

1. TYPE 1A (BULLET CAMERA) DETECTORS ARE GENERALLY USED FOR LARGE MAST ARM INSTALLATION OR WHERE ADVANCE DETECTION IS REQUIRED. DETECTORS USUALLY INSTALL ONE PER APPROACH. TYPE 1B (FISHEYE CAMERA) DETECTORS ARE GENERALLY USED FOR SPAN WIRE DETECTION. DETECTORS ARE USUALLY USED ONE CAMERA PER INTERSECTION.
2. CAMERA SHOULD BE MOUNTED AT LEAST 35' HIGH WHEN USING TALL SHAFTS AND NO LESS THAN 22' WHEN USING SHORT SHAFTS.
3. MAST ARM MOUNTS ARE ONLY ACCEPTABLE IF THE CAMERA CAN BE LOCATED NEAR THE CENTER WITH NO OCCLUSION.
4. CAMERA MUST BE LESS THAN 75' FROM THE INTERSECTION CENTER WHEN MOUNTED ON LAMPHARE ARM WITH NO MORE THAN 100' FROM THE INTERSECTION CENTER ON MAST ARM WITH NO MORE THAN 100' FROM FURTHEST STOP BAR.
5. CAMERA SHOULD BE LOCATED IN FRONT OF ALL STOP LINES WITH LEAST ANGLE OF 10° OCCLUSION.
6. INSTALLER SHALL ADVISE FOR BEST "HEAD-ON" VIEW OF ALL APPROACHES.
7. CAMERA RESISTANCE TO GROUND EQUAL TO OR LESS THAN 25 OHMS.
8. FISHEYE CAMERA HAS APPROXIMATELY 150° TRACKING RANGE. MOUNTED ON MAST ARM, DETECTOR CAN COVER APPROXIMATELY 100' OF APPROACH LANE.

FISHEYE TYPE 1B CAMERA MOUNTING BRACKET (SHEPPARD'S HOOK)



NOTE


TYPICAL BEN: ALIGNMENT FOR TYPE 1A VIDEO DETECTION CAMERA TO BE USED FOR ADVANCE DETECTION ON THE CAMERA MOUNTING BRACKET. THE CAMERA MOUNTING BRACKET SHALL BE LOCATED BETWEEN THE THROUGH LANES FOR 3 LANE APPROACH OR CENTERING TOTAL APPROACH LANE FOR 2 LANE APPROACH LANE.

TYPE 1 VIDEO SENSOR CAMERA PLACEMENT

NOT TO SCALE

STOP BAR DETECTION ZONE - 200' TYP. FOR FISHEYE CAMERA

AS FAR AS POSSIBLE FOR BULLET CAMERAS TO GET ADVANCE DETECTION



TURN LANE DETECTION ZONE - BEGINNING OF TURN LANE TO STOP BAR ON 120' TYP

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

FOR ADVANCE DETECTION

TYPE 1B FISHEYE CAMERA BRACKET



NOTE

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA



NOTE

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA



NOTE

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA


TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA



NOTE

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA


TYPE 1B FISHEYE CAMERA

TYPE 1B FISHEYE CAMERA


TYPE 1B FISHEYE CAMERA

Appendix B

Example Pole and Mast Arm Drawings



730F000(B)



ITEM NO.	PART NUMBER	DESCRIPTION	QTY PER	ASSY	FINISH
1	1064551	WELDING POLE SIG 165 FLU 5/16X280/160 (1/4" X 5/16" X 1/4" X 1/4")	1		R
2	1064555	WELDING ARM SIG RD CURVED 5/16X16X300 (1/4" X 5/16" X 1/4" X 1/4")	1		R
3	1064557	WELDING ARM SIG RD 3/16X16X300 (1/4" X 3/16" X 1/4" X 1/4")	1		R
4	1064558	WELDING ARM SIG RD CURVED 1/4X16X300 (1/4" X 1/4" X 1/4" X 1/4")	1		R
5	1604579	WELDING ARM SIG RD CURVED 1/4X16X300 (1/4" X 1/4" X 1/4" X 1/4")	1		R
6	1800173-75	CAP CAP PHS 6/75 7.25 POLE DIA	2		R
7	1800261	COVER HH M16 3/8 FORMED	1		R
8	1900029-CV	COVER HH M16 4/8	1		R
9	1900030	LATCH HH M16 4/8	1		R
10	1900031	LATCH HH M16 3/8	1		R
11	1900210	STAMPED POLE CAP WELDMENT (13.25-14.75)	1		R
12	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
13	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
14	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
15	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
16	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
17	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
18	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
19	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
20	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
21	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
22	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
23	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
24	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
25	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R
26	1801231-6-10K137L	BOLT HE-HD 3/4-10NC X 13" A320GV	1		R

REV	DESCRIPTION	DATE	DRN
1			

MATERIAL SPECIFICATIONS	
POST: ASTM A570 GR50	
ARM: ASTM A570 GR50	
WELDING: E7018	
ANCHORING: ASTM A499 GR50	
ANCHORING: ASTM A499 GR50	
ANCHORING: ASTM A499 GR50	

DESIGN CRITERIA	
200F MAST ARM	
200F MAST ARM	
200F MAST ARM	
200F MAST ARM	
200F MAST ARM	





WELD SPECIFICATION	
THE POST AND MAST ARM TO BE TAPERED TUBES FABRICATED WITH ONE SUBMITTERED ARC LONGITUDINAL SEAM WELD WITH 100% PENETRATION & TIG WELD FROM BASE PLATE AND JOINT FOR REMAINING. GAL METAL AND WELDING PROCESS WITH JOINT PENETRATION MAY BE USED FOR REMAINING OF WELDING FABRICATION.	
WELD TESTING: 100% OF ALL WELDS VISUAL TESTED (VT) 100% OF ALL COMPLETE JOINT PENETRATION (CJP) WELDS. ULTRASONIC (UT) TESTED (UT) BASED ON THE THINNESS MATING MATERIAL. FOR A570 2013 1/2 S WELD JOINT WELDING. 4" MAX (2" MIN) 1/2" A WANDON 30% OF ALL JOINT WELDS AND PARTIAL JOINT PENETRATION OF JOINT LONGITUDINAL SEAM WELDS WELDING PARTICLES ELSED TIME.	

FINISH SPECIFICATION	
DAILY OR PERM COAT: HOT DIP GALV PER ASTM A123	
FINISH COAT: PAINT	
COLOR: VERMILION	
FEDERAL OR PAL SPEC: 7242-6	
WEIGHT WIGALV-SPRINT: 7242-6	
SURFACE AREA: 143,177.3	
PAINT: 5.37142	





MILLERBERND		1224 N. ST. SO.	WHOLESALE, MIN. 500YD
THE DOCUMENT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF MILLERBERND AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF MILLERBERND AND.			
SALES ORDER NO:	QTY	STATE	DATE
205809	1	AL	1 OF 1
DESCRIPTION:			
SUB POLE SIG 165 FLU TW 5/16X280/160 W/500 & 350 CURVED MAST ARMS			
EST. NO:	DRAWING NO		
7242.4	205809-6		
PROJECT NAME:			
PO 23-15576/ALDOT Mobile Co. McCrager Roundabout/			
SLTS 6-2172			
PROJECT LOCATION:			
DRAWN BY:	DATE:	02-21-2023	
CHK BY:	DATE:		



3/1/23



3/1/23



ITEM NO.	PART NUMBER	DESCRIPTION	QTY
1	1002287	RING BACKUP RD 1/4X17 5/16	1
2	1007303	Flush Outlet Mounting Plate	1
3	1059191	BASE RD 2 x 31"	1
4	1046543	MTG PL RECT 2 X25X31 7/16"	2
5	1046552	SHAFT SCRT 1/65 FLU 5/16X18 0X12.82X37-3	1
6	1046553	GUSSET RING TOP TW 1/65 FLU 3/8X37	1
7	1046554	GUSSET RING Btm TW 1/65 FLU 3/8X37	1
8	1046447	GUSSET TRAP 3/8X24 1/4" OF RSE	2
9	8600254	WLDMT FRAME HH MTL 436 1/2X61 1/2X2P 5/8XNU	1
10	8600272	FRAME HH MTL 3X3 1/2X61 1/2X2P (D-3'X5.25)	1
11	8600808	WIRE GUIDE RING 3/8X2 1/4XOD	2
12	8600922	2" SCH 40 11' LONG	2
13	9900531	S-HOOK (REF 500A158-1)	1
14	9900275	1" SCH 40 PIPE (1 5/16 OD) X 3' LG	1

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF MILLERBERND WFG. AND MAY NOT BE COPIED, REPRODUCED OR DISCLOSED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF MILLERBERND WFG.

422 4TH ST. SO. WINSTED, MN 55395

MILLERBERND

WLDMT POLE SIG 1/65 FLU 5/16X28'0/16'0 (5/16X18.0X14.08X28'0)




DWN: JEFF A. DATE: 02-21-2023

CHK BY: DAIE:

MATERIAL: SEE BOM

WBCHE: 2939.7 LBS. SURFACE AREA: 44685.5 SQ IN SCALE: 1:52 DRWG NO.: 1066551 SHEET: 1 OF 1 **B**

REVISIONS			
REV	CHNG#	DESCRIPTION	DATE



DETAIL - MASTARM SLIP JOINT

REV NO	PART NUMBER	DESCRIPTION	QTY
1	1002224	RING BACKUP 1/4X14.5/16	1
2	1066556	SHAFT RD CHMFR S1 5/16X17 DX10.72X30-1"	1
3	1058316	MTG PL ARM SQ 2" X 25"	1

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF MILLERBERND. NO PART MAY BE REPRODUCED OR TRANSMITTED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT FROM MILLERBERND AGO.

OWN: JEFF A. DATE: 02-21-2023

CHK BY: DATE:

MATERIAL: SEE BOM

WEIGHT: 1618.9 LBS. SURFACE AREA: 30571.3 SQ IN. SCALE: 1:96



DRWG NO: 1066555

DESCRIPTION: WLDMT ARM SIG RD CURVED S1 5/16X300 (5/16X15.0X110.72X307)

SHEET 1 OF 1

B

REVISIONS			
REV	DESCRIPTION	DATE	BY



DETAIL - MAST ARM SUP JOINT

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	1046389	BAR CABLE SUPPORT 3/8 X 6.625	1
2	1046632	SHAFT RD S2 3/16X11.63X7.15X32'-0	1

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF MILLERBERND INC. AND MAY NOT BE COPIED, REPRODUCED OR DISCLOSED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF MILLERBERND INC.

DWN: JEFF A. DATE: 02-21-2023

CHK BY: DATE:

MATERIAL: SEE BOM

WEIGHT: 22323.83 LBS. SURFACE AREA: 50 SQ IN SCALE: 1:30


DRWG NO: 1066557

SHEET 3 OF 3

MILLERBERND 622 6TH ST. SO. WINSTED, MN 55395

WLDMT ARM SIG RD S2 3/16X32'0 (3/16X11.63X7.15X32'-0)


B



		SOUTH COAST LIGHTING & DESIGN 232 AVENIDA FABRICANTE, STE. 109 SAN CLEMENTE, CA 92672 PH 949 276 8850 FX 949 276 8855 SALES@SOUTHCOSTLIGHTING.COM	
5/27/2018 MK MK MK MK		BCHUN4851	
ALUMINUM		R-062718-2P	
N/A		BASES	



3/1/23



NOTES:

1. ANCHOR BOLT PER ASTM F1554 GRADE 55 S1 & OR AASHTO M314-90 GRADE 55. YIELD STRENGTH = 55,000 PSI MIN YIELD TENSILE STRENGTH = 75,000-95,000 PSI
2. FULLY HOT DIP GALVANIZE PER ASTM A153.
3. THREAD TO BE CLASS 2A PER AMERICAN STD. B 1.1 .030 OVER SIZE AFTER GALVANIZING
4. ALL BOLTS ROLLED THREAD
5. GALVANIZED HEAVY HEX NUTS (A563GV) PER ASTM A563 OR 1H .030 OVER SIZE) OR GA194 2H EQUIVALENT
6. NO WELDING IS ALLOWED ON ANCHOR BOLTS
7. GALVANIZED FLAT WASHERS PER ASTM F436.
8. GALVANIZED LOCKWASHERS
9. THE END OF ANCHOR BOLT TO PROJECT FROM THE CONCRETE PAINTED PER COLOR CODE

PART NO BOLT QWL7	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	PART NO BOLT W/2 NUTS, 2 LOCK & 2 FLAT WASHERS	"A"	CL	"B" THD SIZE	"C" THD SIZE	"L"	"D"	"R"	COLOR CODE	QTY BOLTS	QTY NUTS	QTY LOCK WASHERS	QTY FLAT WASHERS
460A579-1	460A579-1THV	460A579-1THV	460A579-1THV	460A579-1THV	460A579-1THV	460A579-1THV	460A579-1THV	460A579-1THV	460A579-1THV	3/8	48"	1-8	8"	36"	4"	2 1/2	YELLOW				
460A579-2	460A579-2THV	460A579-2THV	460A579-2THV	460A579-2THV	460A579-2THV	460A579-2THV	460A579-2THV	460A579-2THV	460A579-2THV	1/2	48"	1 1/4-7	8"	42"	6"	2 1/2	YELLOW				
460A579-3	460A579-3THV	460A579-3THV	460A579-3THV	460A579-3THV	460A579-3THV	460A579-3THV	460A579-3THV	460A579-3THV	460A579-3THV	3/4	60"	1 1/2-6	10"	54"	8"	3 3/8	YELLOW				
460A579-4	460A579-4THV	460A579-4THV	460A579-4THV	460A579-4THV	460A579-4THV	460A579-4THV	460A579-4THV	460A579-4THV	460A579-4THV	1	84"	2-4	12"	84"	8"	3 1/2	YELLOW	41	82	41	82
460A579-5	460A579-5THV	460A579-5THV	460A579-5THV	460A579-5THV	460A579-5THV	460A579-5THV	460A579-5THV	460A579-5THV	460A579-5THV	1 1/4	96"	2-4	12"	96"	8"	4	YELLOW				
460A579-6	460A579-6THV	460A579-6THV	460A579-6THV	460A579-6THV	460A579-6THV	460A579-6THV	460A579-6THV	460A579-6THV	460A579-6THV	1 1/2	96"	2-4	12"	96"	8"	4	YELLOW				
460A579-7	460A579-7THV	460A579-7THV	460A579-7THV	460A579-7THV	460A579-7THV	460A579-7THV	460A579-7THV	460A579-7THV	460A579-7THV	1 3/4	96"	2-4	12"	96"	8"	4	YELLOW				
460A579-8	460A579-8THV	460A579-8THV	460A579-8THV	460A579-8THV	460A579-8THV	460A579-8THV	460A579-8THV	460A579-8THV	460A579-8THV	2	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-9	460A579-9THV	460A579-9THV	460A579-9THV	460A579-9THV	460A579-9THV	460A579-9THV	460A579-9THV	460A579-9THV	460A579-9THV	2 1/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-10	460A579-10THV	460A579-10THV	460A579-10THV	460A579-10THV	460A579-10THV	460A579-10THV	460A579-10THV	460A579-10THV	460A579-10THV	2 1/2	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-11	460A579-11THV	460A579-11THV	460A579-11THV	460A579-11THV	460A579-11THV	460A579-11THV	460A579-11THV	460A579-11THV	460A579-11THV	2 3/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-12	460A579-12THV	460A579-12THV	460A579-12THV	460A579-12THV	460A579-12THV	460A579-12THV	460A579-12THV	460A579-12THV	460A579-12THV	3	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-13	460A579-13THV	460A579-13THV	460A579-13THV	460A579-13THV	460A579-13THV	460A579-13THV	460A579-13THV	460A579-13THV	460A579-13THV	3 1/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-14	460A579-14THV	460A579-14THV	460A579-14THV	460A579-14THV	460A579-14THV	460A579-14THV	460A579-14THV	460A579-14THV	460A579-14THV	3 1/2	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-15	460A579-15THV	460A579-15THV	460A579-15THV	460A579-15THV	460A579-15THV	460A579-15THV	460A579-15THV	460A579-15THV	460A579-15THV	3 3/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-16	460A579-16THV	460A579-16THV	460A579-16THV	460A579-16THV	460A579-16THV	460A579-16THV	460A579-16THV	460A579-16THV	460A579-16THV	4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-17	460A579-17THV	460A579-17THV	460A579-17THV	460A579-17THV	460A579-17THV	460A579-17THV	460A579-17THV	460A579-17THV	460A579-17THV	4 1/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-18	460A579-18THV	460A579-18THV	460A579-18THV	460A579-18THV	460A579-18THV	460A579-18THV	460A579-18THV	460A579-18THV	460A579-18THV	4 1/2	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-19	460A579-19THV	460A579-19THV	460A579-19THV	460A579-19THV	460A579-19THV	460A579-19THV	460A579-19THV	460A579-19THV	460A579-19THV	4 3/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-20	460A579-20THV	460A579-20THV	460A579-20THV	460A579-20THV	460A579-20THV	460A579-20THV	460A579-20THV	460A579-20THV	460A579-20THV	5	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-21	460A579-21THV	460A579-21THV	460A579-21THV	460A579-21THV	460A579-21THV	460A579-21THV	460A579-21THV	460A579-21THV	460A579-21THV	5 1/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-22	460A579-22THV	460A579-22THV	460A579-22THV	460A579-22THV	460A579-22THV	460A579-22THV	460A579-22THV	460A579-22THV	460A579-22THV	5 1/2	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-23	460A579-23THV	460A579-23THV	460A579-23THV	460A579-23THV	460A579-23THV	460A579-23THV	460A579-23THV	460A579-23THV	460A579-23THV	5 3/4	120"	2-4	12"	120"	8"	4	YELLOW				
460A579-24	460A579-24THV	460A579-24THV	460A579-24THV	460A579-24THV	460A579-24THV	460A579-24THV	460A579-24THV	460A579-24THV	460A579-24THV	6	120"	2-4	12"	120"	8"	4	YELLOW				

REV 12/22/22 ADDED -34 & -35 TO CHART OHS
REV 02/28/19 CHANGED ALL A.S. TO FULLY GALVANIZED TX
REV 2-16-18 ADDED SHEET -29 TO CHART - JD
REV 1-9-17 ADDED SHEET -2 AND -25 AND -26 TO CHART
REV 12-16-16 ADDED -22, -23 AND -24 TO CHART
REV 12-8-16 ADDED 460A579-2
REV 2-29-15 -15 "L" WAS 54"
REV 6-30-15 ADDED 460A579-13
REV 9-6-13 -9 CL WAS 48"
REV 11-20-11 CHANGED "C" ON "1 FROM 8" TO 6",
"C" ON "3, 4 & 5 FROM 12" TO 10" AND "L" ON
"6 FROM 96" TO 84" AND "9 FROM 6" TO 7"

DWN: JAMIE D.

DATE: 08-16-11

CHK: FLOYD F.

SCALE: NTS

ANCHOR BOLTS


F1554 GRADE 55 FULLY GALV

Millerbernd MANUFACTURING CO.
WINSTED, MN

SHEET 1 OF 2
460A579

730FOOT (B)

ITEM NO.	PART NUMBER	DESCRIPTION	QTY PER	ASSY	FINISH
1	1066541	WLDMT POLE SEC 1AS F.U. 3/8X3/21/6 G (21/6X16 2X12 803370)	1		R
2	1066545	WLDMT ARM SEC 425 CURVED 1/4X43/0 (1/4X43 0X4 475457)	1		R
3	1066548	WLDMT ARM SEC 425 CURVED ST 5/16X33/0 (5/16X33 0X11 720327)	1		R
4	1066550	WLDMT ARM SEC 425 ST 3/16X37/0 (3/16X37 0X11 720327)	1		R
5	460457P-DHPW	A87-W211554CRSS W/2CVNUT,2FL	8	2EF	
6	8800193-6	CAP CAP FTS 525 - 575 POL E DIA	1		R
7	8800193-75	CAP CAP FTS 675 - 775 POL E DIA	1		R
8	8800267	COVER HH M15 3XS FORMED	1		R
9	9900079-GV	COVER HH M15 6 4X6	1		R
10	9900030	LATCH HH M15 8 8X8	1		R
11	9900037	LATCH HH M15 3XS	1		R
12	9900209	STAMPED POLE CAP WELDMENT (11 75-13 25)	1		R
13	8011A2/B-108137L	BOLT HK HD 3-6-12NC X 1/2 AS370CV	1		R
14	8011A2/B-16X3/AA	BOLT HK HD 3-6-16NC X 3/4 S-4330CV	1		R
15	801781-1/7-6X4-1/2B	BOLT HHV-HDD 1-1-2-4 X 4-1-2 A320CV	12		R
16	EL-20-2	GFO 20AMP P4320FS-FWRVR	2		R
17	EL-50-1	GFO RECTIFIABLE COVER (MG35) PH CKSVU	1		R
18	NUT HH 3-6-12NC GS-GV	NUT HH 3-6-12NC GS-GV	1		R
19	ICRWAA HK 56 FL HD 5-16-16NC X 2 35	ICRWAA HK 56 FL HD 5-16-16NC X 2 35	1		R



REVISIONS			
REV.	DESCRIPTION	DATE	DWTR

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	1004052	RING BACKUP 1/4"X1/4"	1
2	1007303	Rush Outlet Mounting Plate	1
3	1009191	BASE RD 2 x 31"	1
4	1066543	SHAFT SCRI 1/8 FLU 3/8X18.0X12.82X37'-0	1
5	1066544	WIG PL REC1 2'X25'X31 7/16"	2
6	1066544	QUISSET RING TOP TW 1/8 FLU 1/2X25	1
7	1066545	QUISSET RING BSM TW 1/8 FLU 1/2X32	1
8	1066591	QUISSET TRAP 1/2X25X1/4 1/2" RISE	2
9	3800256	WLDMT FRAME HH M16 4X5 1/21X1 1/2DP 3/8 NUT	1
10	3800272	FRAME HH M15 3X5 1/21X1 1/4DP (RD-3'X5.25)	1
11	3800206	WIRE GUIDE RING 3/8X2 1/4OD	2
12	3800922	PIPE ACCESSORY 3/8X2 1/4V	2
13	9900051	S-HOOK (REF 500A156 1)	1
14	9900275	1" SCH 40 PIPE (1 5/16 OD) X 3' LG	1

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF MILLERBERND. IT IS TO BE KEPT IN STRICTLY CONFIDENTIAL AND MAY NOT BE COPIED, REPRODUCED, OR DISCLOSED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF MILLERBERND INC.

OWN: JEFF A. DATE: 02-20-2023

CHK BY: DATE:

MATERIAL: SEE BOM


WEIGHT: 3811.6 LBS. SURFACE AREA: 54020.6 SQ IN. SCALE: 1:52

DRWG NO: 1066541



SHEET 1 OF 1

B





REVISIONS			
REV	CHNG#	DESCRIPTION	DATE






ITEM NO	PART NUMBER	DESCRIPTION	QTY
1	1002292	RING BACKUP RD 1/4X15 5/16	1
2	1066549	SHAFT RD CHMFR S1 5/16X16.0X11.02X35-7	1
3	1058316	MTG PL ARM SQ 2" X 25"	1

DWN: JEFF A.	DATE: 02-20-2023	DESCRIPTION: WLDMT ARM SIG RD CURVED S1 5/16X35" (5/16X16.0X11.02X35"7)
CHK BY:	DATE:	
MATERIAL:	SEE BOM	
WEIGHT: 1907.6 LBS	SURFACE AREA: 37080.0 SQ IN	SCALE: 1:96
DRWG NO: 1066548	SHEET 1 OF 1	B

REVISIONS			
REV.	DESCRIPTION	DATE	BY

APPROVED



DETAIL A
SCALE 1:8




3/1/23

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	1047437	BAR CABLE SUPPORT 3/8 X 6.25	1
2	1066550	SHUTT RD S2 3/16X11.93X6.75X37-0	1

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF MILLERBERND. IT IS NOT TO BE COPIED, REPRODUCED, OR DISCLOSED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF MILLERBERND.	MILLERBERND 4500 18TH ST. S.O. WINSTED, IAN 55395
---	--

DWN: JEFF A. DATE: 02-20-2023 CHK BY: DATE: MATERIAL: SEE BOM	DESCRIPTION: WLDMT ARM SIG RD S2 3/16X37-0 (3/16X11.93X6.75X37-0)
WEIGHT: LBS. SURFACE AREA: 25667.64 SQ IN SCALE: 1:30	DRWG NO.: 1066550 SHEET: B OF 1




3/1/23

QTY:2

		SOUTH COAST LIGHTING & DESIGN 232 AVENIDA FABRICANTE, STE. 109 SAN CLEMENTE, CA 92672 PH: 949 276 8850 FAX: 949 276 8855 SALES@SOUTHCOSTLIGHTING.COM	
DATE: 3/27/2018 BY: MK CHECKED: JS APPROVED: MK	PROJECT: BCUHUN4851 DESCRIPTION: ALUMINUM MATERIAL: ALUMINUM FINISH: N/A	ORDER NO: R-062718-2P QUANTITY: 2 UNIT: Bases	1 of 1



3/1/23



NOTES:

1. ANCHOR BOLT PER ASTM F1554 GRADE 55 S1 &/OR AASHTO M314-90 GRADE 55. YIELD STRENGTH = 55,000 PSI MIN YIELD TENSILE STRENGTH = 75,000-95,000 PSI
2. FULLY HOT DIP GALVANIZE PER ASTM A153.
3. THREAD TO BE CLASS 2A PER AMERICAN STD. B 1.1 .030 OVER SIZE AFTER GALVANIZING
4. ALL BOLTS ROLLED THREAD

5. GALVANIZED HEAVY HEX NUTS (A563GV) PER ASTM A563 GR 5H (030 OVER SIZE) OR (A194 2H EQUIVALENT)
6. NO WELDING IS ALLOWED ON ANCHOR BOLTS
7. GALVANIZED FLAT WASHERS PER ASTM F436
8. GALVANIZED LOCKWASHERS
9. THE END OF ANCHOR BOLT TO PROJECT FROM THE CONCRETE PAINTED PER COLOR CODE

PART NO BOLT CODE	PART NO BOLT V/3 NUTS & 2 FLAT WASHERS	PART NO BOLT V/3 NUTS & 2 FLAT WASHERS	PART NO BOLT V/2 NUTS & 2 FLAT WASHERS	PART NO BOLT V/2 NUTS & 2 FLAT WASHERS	PART NO BOLT V/2 NUTS & 2 FLAT WASHERS	PART NO BOLT V/2 NUTS	PART NO BOLT V/1 NUT	'A'	CL	'B' THD SIZE	'C' DT HX THD LG	'L'	'D'	'R'	COLOR CODE	QTY BOLTS	QTY NUTS	QTY LOCK WASHER	QTY FLAT WASHERS
460A579-1	460A579-1THV	460A579-1THV	460A579-1DNV	460A579-1DNV	460A579-1DNV	460A579-1DNV	460A579-1N	.06	48"	1-8	6"	36"	4"	2 1/2	YELLOW				
460A579-2	460A579-2THV	460A579-2THV	460A579-2DNV	460A579-2DNV	460A579-2DNV	460A579-2DN	460A579-2N	1.148	48"	1 1/4-7	8"	42"	6"	2 1/2	YELLOW				
460A579-3	460A579-3THV	460A579-3THV	460A579-3DNV	460A579-3DNV	460A579-3DNV	460A579-3DN	460A579-3N	1.381	60"	1 1/2-6	10"	54"	6"	3 3/8	YELLOW				
460A579-4	460A579-4THV	460A579-4THV	460A579-4DNV	460A579-4DNV	460A579-4DNV	460A579-4DN	460A579-4N	1.613	90"	1 3/4-5	10"	84"	6"	3 1/2	YELLOW				
460A579-5	460A579-5THV	460A579-5THV	460A579-5DNV	460A579-5DNV	460A579-5DNV	460A579-5DN	460A579-5N	1.845	90"	2-4 1/2	10"	84"	6"	4"	YELLOW	41	82	41	82
460A579-6	460A579-6THV	460A579-6THV	460A579-6DNV	460A579-6DNV	460A579-6DNV	460A579-6DN	460A579-6N	2.148	96"	2 1/4-4 1/2	12"	89"	7"	4 1/2	YELLOW				
460A579-7	460A579-7THV	460A579-7THV	460A579-7DNV	460A579-7DNV	460A579-7DNV	460A579-7DN	460A579-7N	1.845	96"	2-4 1/2	10"	90"	6"	4"	YELLOW				
460A579-8	460A579-8THV	460A579-8THV	460A579-8DNV	460A579-8DNV	460A579-8DNV	460A579-8DN	460A579-8N	1.148	48"	1 1/4-7	6"	36"	4"	2 1/2	YELLOW				
460A579-9	460A579-9THV	460A579-9THV	460A579-9DNV	460A579-9DNV	460A579-9DNV	460A579-9DN	460A579-9N	1.148	31"	1 1/4-7	6"	43"	6"	2 1/2	YELLOW				
460A579-10	460A579-10THV	460A579-10THV	460A579-10DNV	460A579-10DNV	460A579-10DNV	460A579-10DN	460A579-10N	1.381	60"	1 1/2-6	10"	60"	6"	3 3/8	YELLOW				
460A579-11	460A579-11THV	460A579-11THV	460A579-11DNV	460A579-11DNV	460A579-11DNV	460A579-11DN	460A579-11N	1.148	48"	1 1/4-7	10"	42"	6"	2 1/2	YELLOW				
460A579-12	460A579-12THV	460A579-12THV	460A579-12DNV	460A579-12DNV	460A579-12DNV	460A579-12DN	460A579-12N	1.381	60"	1 1/2-6	10"	54"	6"	3 3/8	YELLOW				
460A579-13	460A579-13THV	460A579-13THV	460A579-13DNV	460A579-13DNV	460A579-13DNV	460A579-13DN	460A579-13N	.06	42"	1-8	6"	36"	4"	2 1/2	YELLOW				
460A579-14	460A579-14THV	460A579-14THV	460A579-14DNV	460A579-14DNV	460A579-14DNV	460A579-14DN	460A579-14N	1.845	60"	2-4 1/2	10"	60"	6"	4"	YELLOW				
460A579-15	460A579-15THV	460A579-15THV	460A579-15DNV	460A579-15DNV	460A579-15DNV	460A579-15DN	460A579-15N	1.148	34"	1 1/4-7	9"	48"	6"	2 1/2	YELLOW				
460A579-16	460A579-16THV	460A579-16THV	460A579-16DNV	460A579-16DNV	460A579-16DNV	460A579-16DN	460A579-16N	.01	96"	1-8	6"	90"	4"	2 1/2	YELLOW				
460A579-17	460A579-17THV	460A579-17THV	460A579-17DNV	460A579-17DNV	460A579-17DNV	460A579-17DN	460A579-17N	1.381	90"	1 1/2-6	10"	84"	6"	3 3/8	YELLOW				
460A579-18	460A579-18THV	460A579-18THV	460A579-18DNV	460A579-18DNV	460A579-18DNV	460A579-18DN	460A579-18N	.01	46"	1-8	6"	42"	4"	2 1/2	YELLOW				
460A579-19	460A579-19THV	460A579-19THV	460A579-19DNV	460A579-19DNV	460A579-19DNV	460A579-19DN	460A579-19N	1.381	80"	1 1/2-6	10"	72"	6"	3 3/8	YELLOW				
460A579-20	460A579-20THV	460A579-20THV	460A579-20DNV	460A579-20DNV	460A579-20DNV	460A579-20DN	460A579-20N	1.148	90"	1 1/4-7	10"	84"	6"	2 1/2	YELLOW				
460A579-21	460A579-21THV	460A579-21THV	460A579-21DNV	460A579-21DNV	460A579-21DNV	460A579-21DN	460A579-21N	1.613	80"	1 3/4-5	10"	72"	6"	3 1/2	YELLOW				
460A579-22	460A579-22THV	460A579-22THV	460A579-22DNV	460A579-22DNV	460A579-22DNV	460A579-22DN	460A579-22N	1.148	96"	1 1/4-7	12"	90"	6"	2 1/2	YELLOW				
460A579-23	460A579-23THV	460A579-23THV	460A579-23DNV	460A579-23DNV	460A579-23DNV	460A579-23DN	460A579-23N	1.381	96"	1 1/2-6	12"	90"	6"	3 3/8	YELLOW				
460A579-24	460A579-24THV	460A579-24THV	460A579-24DNV	460A579-24DNV	460A579-24DNV	460A579-24DN	460A579-24N	1.613	96"	1 3/4-5	12"	90"	6"	3 1/2	YELLOW				

REV 12/12/22 ADDED -34 & -35 TO CHART QSD
REV 2/2/23 CHANGED ALL A.S. TO FULLY GALVANIZED TK
REV 2-16-18 ADDED SHEET -34 TO CHART -30
REV 1-9-17 ADDED SHEET 3 AND -25 AND -26 TO CHART
REV 12-16-16 ADDED -22, -23 AND -24 TO CHART
REV 12-8-16 ADDED 460A579-21
REV 9-29-15 1/8 "L" WAS 5/4"
REV 6-30-15 ADDED 460A579-13
REV 9-4-13 -9 CL WAS 40"
REV 11-28-11 CHANGE "C" ON -1 FROM 8" TO 6",
"C" ON -3, -4 & -5 FROM 12" TO 10" AND "L" ON
-4 FROM 56" TO 89" AND 10" FROM 6" TO 7"

DWN: JAMIE D.

DATE: 08-16-11

CHK: FLOYD F.

SCALE: NTS

ANCHOR BOLTS

F1554 GRADE 55 FULLY GALV

Millerbernd


MANUFACTURING CO.
WINSTED, MN

SHEET 1 OF 2
460A579




















PROCUREMENT DEPARTMENT

Potential bidders are responsible to check this site for any ADDENDUMS that are issued. It is the responsibility of the BIDDER to check for, download, and include with their BID RESPONSE any and all ADDENDUMS that are issued for a specific BID published by the City of Mobile. Failure to download and include ADDENDUMS in your BID RESPONSE may cause your bid to be rejected.

This is a sealed bid. Any responses faxed or emailed will be rejected.

This is a sealed bid. Any response must be submitted in a sealed envelope with the bid number and bid opening date on the outside of the envelope.

Any response that arrives improperly marked or with no bid number and opening date on the outside of the delivery or express package and opened in error will be rejected and not considered.

It is the responsibility of the bidder to ensure that their bid response is delivered to and received in the Purchasing Department before the date and time of the bid opening.

Please read the Terms and Conditions.

All bids are F.O.B. destination unless otherwise stated.

Please sign your bid.

Package/Bid Delivery Address (Request First Delivery):
Purchasing Department
205 Government St., RM S408
Mobile, AL 36644