

SEALED BID

CITY OF MOBILE

BID SHEET

Do Not Return Via Email or Fax

Mailing Address:
P. O. Box 1948
Mobile, Alabama 36633
(251) 208-7434

Purchasing Department
and Package Delivery:
Bid Delivery Address:

Government Plaza
4th Floor, Room S-408
205 Government St.
Mobile, Alabama 36644

Postal Service Does Not Deliver to This Street Address

This is Not an Order

**READ TERMS AND CONDITIONS
ON REVERSE SIDE OF THIS PAGE
BEFORE BIDDING**

Typed by: lw

Buyer: 002

Please quote the lowest price at which you will furnish the articles listed below

DATE	BID NO.	DEPARTMENT	Commodities to be delivered F.O.B. Mobile to:
8/18/2026	6067	MOTOR POOL	BROAD STREET

This bid must be received and stamped by the Purchasing office not later than: 12:01 P.M., WEDNESDAY, SEPTEMBER 9, 2026

QUANTITY	ARTICLES	UNIT	UNIT PRICE		EXTENSION	
			Dollars	Cents	Dollars	Cents
	3/4 TON EXTENDED CAB TRUCK WITH UTILITY BODY					
APPX 2-8	Vendor to provide NEW chassis with Reading Model U98 Body WITH NO LADDER RACK, or equal, already mounted to chassis. Chassis Make_____ Model_____ Body Make_____ Model_____ Provide literature and specifications on product bid. State Warranty _____ Location of Installation _____					
APPX 2-8	Vendor to provide NEW chassis with Reading Model U98 Body WITH LADDER RACK, or equal, already mounted to chassis. Chassis Make_____ Model_____ Body Make_____ Model_____ Provide literature and specifications on product bid. State Warranty _____ Location of Installation _____					
Page 1 of 2			TOTAL			

**RETURN ONE SIGNED COPY OF THIS BID
IN ENCLOSED ENVELOPE**

State delivery time within _____ days of receipt of P.O.

Phone Number _____

Firm Name _____

Email Address _____

Signature _____

Type or Print Name _____

1. All quotations must be signed with the firm name and by an authorized officer or employee.
2. Verify your bid before submission as it cannot be changed or corrected after being opened. In case of error in extension of prices, the unit price will govern.
3. If you do not bid, return this sheet and state reason. Otherwise, your name may be removed from our mailing list.
4. The right is reserved to reject any, or all quotations, or any portions thereof, and to waive technicalities if deemed to be in the interest of the City of Mobile.
5. This bid shall not be reassignable except by written approval of the Purchasing Agent of the City of Mobile.
6. State brand and model number of each item. All items bid must be new and latest model unless otherwise specified.
7. If bid results are desired, enclose a self-addressed and stamped envelope with your bid. (All or None bids only)
8. Do not include Federal Excise Tax as an exemption certificate will be issued in lieu of same. The City is exempt from the State of Alabama and City sales taxes.
9. PRICES ARE TO BE FIRM AND F.O.B. DESTINATION UNLESS OTHERWISE REQUESTED.
10. BID WILL BE AWARDED ON ALL OR NONE BASIS UNLESS OTHERWISE STATED.
11. Bids received after specified time will be returned un-opened.
12. Failure to observe stated instructions and conditions will constitute grounds for rejection of your bid.
13. Furnish literature, specifications, drawings, photographs, etc., as applicable with the items bid.
14. Vendor may be required to obtain City of Mobile Business License as applicable to City of Mobile Municipal Code Section 34-50. For Business License inquiry, contact the Revenue Department at (251) 208-7462 or cityofmobile.org/business-license-overview/
15. IF a bid bond is required in the published specifications, see below:
Each bid shall be accompanied by a **Cashier's Check, Certified Check, Bank Draft or Bid Bond** for the sum of five (5) Percent of the amount bid, made payable to the City of Mobile and certified by a reputable banking institution. All checks shall be returned promptly, except the check of the successful bidder, which shall be returned after fulfilling the bid.
16. Contracts in excess of \$50,000 require that the successful bidder make every possible effort to have at least fifteen (15) percent of the total value of the contract performed by socially and economically disadvantaged individuals.
17. All bids/bid envelopes must have the bid number noted on the front. Bids that arrive unmarked and are opened in error shall be returned to vendor as an unacceptable bid.
18. If successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Alabama Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for and issuance of a Certificate of Authority may be several weeks.
19. Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State to submit a bid, but may need to obtain the Business License and Certificate of Authority if applicable, prior to issuance of a Purchase Order.
20. Bids and addendums are posted at www.cityofmobile.org/services/business/bids/. It is the responsibility of the vendor to check the City's bid page for updates and addendums.
21. Vendors must be able to provide the following upon request. Federal W-9 form, proof of registration in the E-Verify program, and Certificate of Authority to do business in Alabama/Registration with the Alabama Secretary of State within 24 hours of request.
22. City of Mobile applies local vendor preference to all purchases: Code of Alabama, 1975, Sections 41-16-50(a) and 41-16-50(d), except federally funded grants.
23. Equal Employment Opportunity. Except as otherwise provided under 41 CFR part 60, all contracts that meet the definition of "federally assisted construction contract" in 41 CFR Part 60-1.3 must include the equal opportunity clause provided under 41 CFR 60-1.4(b), in accordance with Executive Order 11246, "Equal Employment Opportunity" (30 FR 12319, 12935, 3 CFR Part, 1964-1965 Comp., p. 339), as amended by Executive Order 11375, "Amending Executive Order 11246 Relating to Equal Employment Opportunity," and implementing regulations at 41 CFR part 60, "Office of Federal Contract Compliance Programs, Equal Employment Opportunity, Department of Labor."
24. Davis-Bacon Act, as amended (40 U.S.C. 3141-3148) will apply when required by Federal program regulations.

BID CONTINUATION SHEET

Page _____ of _____

QUANTITY	ARTICLES	UNIT	UNIT PRICE		EXTENSION	
			Dollars	Cents	Dollars	Cents
	Page 2 of 2 All vendors will be required to provide verification of enrollment in the E-Verify program. Additional information may be found at http://immigration.alabama.gov/ If the successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See: www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for the issuance of a Certificate of Authority may be several weeks. Upon notification, vendor will have 10 business days to provide the Certificate of Authority and the E-Verify numbers to the Purchasing Department before award can be completed. (Vendors will possibly need to pay the expedite fee to meet this requirement because application is not sufficient. We must have a copy of the certificate with your Company ID number). Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State, nor the E-Verify for certification to submit a bid, but will need to obtain the Business License and Certificate of Authority verification and/or provide the E-Verify Certification, if applicable, prior to issuance of a Purchase Order. State of Alabama Local Vendor Preference Law 41-16-50 (a) and (d) will apply to this purchase. If you have any questions, please feel free to contact the Purchasing Department at purchasing@cityofmobile.gov. CONE OF SILENCE. From the time of advertising, and until the final award by completion of a signed contract or purchase document issued by the City, there is a prohibition on communication by respondents (or anyone on their behalf) with the City staff and elected officials regarding this request for bids, proposals, or qualifications. This does not apply to communications directly with the Procurement Department staff during authorized question periods, or with designated City staff during pre-bid conferences, interviews, requests for clarification, and written contract negotiations. Breaking the established prohibition on communication, if proven, may result in a disqualification of your submittal. TO BE AWARDED ALL OR NONE.					
			TOTAL			

**RETURN ONE SIGNED COPY OF THIS QUOTATION
IN ENCLOSED ENVELOPE**

READ ABOVE INSTRUCTIONS BEFORE QUOTING

Firm Name _____

By _____

CHASSIS SPECIFICATIONS

	YES	NO
1. 3/4-TON 2-WHEEL DRIVE CHASSIS		
2. EXTENDED CAB		
3. GASOLINE ENGINE		
4. POWER WINDOWS, MIRRORS, AND DOOR LOCKS		
5. SINGLE REAR AXLE		
6. ALL WEATHER TIRES		
7. AIR CONDITIONING		
8. VINYL SEATS		
9. POWER INVERTER 120V/400 WATT MOUNTED IN CAB IN MIDDLE OF FLOOR BOARD		
10. CHASSIS COLOR TO BE WHITE		
11. TOWING PACKAGE		
12. SPARE TIRE WITH CRANK DOWN STORAGE		
13. CAB TO AXLE – 56 INCHES		
14. FACTORY-MOUNTED STEPS OR RUNNING BOARD		

Chassis shall have a receiver hitch.

Utility body compartments shall have an LED lighting that is switched with a manual toggle switch. Compartment lights may be powered from the truck’s taillight circuit.

Receiver hitch to be accessible.

Rear bumper shall be a recessed frame mounted bumper with center recess to trailer hitch.

Rear bumper recess shall allow for mounting of pintle hitch if City so desires. (Pintle access cut out.)

BODY SPECIFICATIONS

The Following MINIMUM are for a utility body- to be installed on new CAB//CHASSIS with factory receiver hitch. Cab to axle measure is 56 inches. Utility body is 97.25 inches long x 76 inches wide.

	YES	NO
1. Body Shell - The body shell is to be constructed of 14-gauge two-sided A40 Galvanneal steel. The compartment tops and backs are to be a one-piece seamless design. All doors, door openings, drip rails, and other exposed steel edges are to be hemmed for strength, safety, and resistance to corrosion.	_____	_____
2. Floor - The floor plate is to be constructed of a minimum of 12-gauge treadplate with a 13/8" return flange on each side. The side compartment back panel should overlap and interlock with the floor flange, providing support for the weight of the side compartment.	_____	_____
3. Understructure - Cross sills are to be constructed from 1 1/2-gauge steel with 50,000 psi minimum yield strength.	_____	_____
4. Tailgate - The tailgate is to be constructed of 14-gauge two-sided A40 Galvanneal steel. The tailgate is to be a minimum of 12 "high and be a slammable style.	_____	_____
5. Doors - The doors are to be constructed of 20-gauge two-sided A40 Galvanneal steel. The doors are to be double paneled with hat section reinforcements.	_____	_____
6. Hinges - Corrosion resistant all stainless steel continuous hinges are to be installed to provide full length support for the doors and pry-proof security with a built-in weather shield. Hinges are to be spot welded to the door frames and must be supported with a six-year warranty .	_____	_____
7. Rotary Latches - Zinc plated corrosion resistant rotary latches are riveted to the doors with non-corrosive aluminum rivets incorporating stainless steel mandrels. The rotary latches are to be slam-latchable. The latching cam is to be elongated to allow the latch to move vertically relative to the lock strike to prevent torsional damage.	_____	_____
8. Door Strikers - Adjustable strikers are to be affixed to the door frames with screws. (Welded-on door strikers are not acceptable.)	_____	_____
9. Door Seals - Automotive "bulb type" neoprene door seals are to be installed by the manufacturer of the body on all door frames.	_____	_____
10. Door Retainers - Double spring over center door retainers are to be installed on all vertical doors. Retainers need to hold doors in positive open or closed position. (Other types of retainers, like cables or chains, are not acceptable.)	_____	_____

11.	Shelving - Shelves are to be constructed of 18-gauge bright spangled galvanized steel. All shelves are to have hemmed dividers on 4" centers. Shelves need to have a minimum capacity rating of 250-lbs.	_____	_____
12.	Shelving - 2 adjustable shelves with dividers street and curbside front vertical 1 adjustable shelf with dividers street and curbside rear vertical 1 adjustable shelf curbside horizontal.	_____	_____
13	Exterior Prime Paint - The body is to be completely immersed in electro deposition gray epoxy prime paint featuring a zinc phosphate pre coat and seal for additional corrosion protection. Prime paint is to be oven cured to provide a hard, durable finish.	_____	_____
14.	Interior Paint - Interior paint is to be a mid-gloss, mar resistant, light gray finish.	_____	_____
15.	Final Paint - Factory painted white inside of compartments and exterior of body.	_____	_____
16.	Undercoating - The body is to be completely undercoated by the body manufacturer using a water base acrylic.	_____	_____
17.	Installation - The manufacturer of the body is to supply a recommended installation process along with detailed installation instructions that conform to all applicable Federal Motor Vehicle Safety Standards. Rear body-to-chassis mounting brackets need to incorporate bumper support as well as provide FMVSS 30 I protection. Furthermore, the manufacturer of the body is to supply an owner manual describing the proper care and maintenance of the body for the user.	_____	_____
18.	Warranty - The following items are to be covered by a minimum six (6) year limited warranty to the first owner/user of record.	_____	_____
19.	No Rust-Thru Guarantee	_____	_____
20.	Continuous Door Hinges -Guaranteed not to fail to operate or come off product.	_____	_____
21.	Latches and Lock Cylinders -Guaranteed against failure.	_____	_____
22.	Shelves -Guaranteed not to fail in bending under a maximum 250 lb. rated load.	_____	_____
23.	Lighting - Lighting is to meet all FMVSS standards. The wiring harness is to be encased in a plastic loom and all wires are to be colored for ease of troubleshooting. The wire harness must have connectors that are compatible with Ford, GM, and Dodge chassis without splicing. The stop/tail/turn and backup lights are to be recessed in the rear of the body. The stop/tail/turn lights are to be clear-back style. The side marker lights are to be recessed in the body drip rail for protection.	_____	_____
24.	Interior Compartment - The rear compartments are to be illuminated from clear back style taillights. All Lighting compartments are to be illuminated with lights powered off taillight circuit. Manual toggle switches are required on each light.	_____	_____

- | | | | |
|-----|---|-------|-------|
| 25. | Lighting Wire - Wires must be retained by a fastening system. | _____ | _____ |
| 26. | Retention Interior Light Guard and Warning Lights - Light guards are to be installed by the body manufacturer to provide protection for recessed stop/tail/turn, backup lights, and warning lights. The wiring harness needs to be protected also. | _____ | _____ |
| 27. | Bumper - Drop step bumper with pintle recess cutout. | _____ | _____ |
| 28. | Ladder rack Kargo Master pipe rack constructed of 2" steel tubing, powder coated with a load rating of 1700 lbs. Cross bars are 62 inches wide. Ladder rack ratchet straps with J-hooks, two (2) on each side. | _____ | _____ |
| 29. | Bed liner Inside of body between compartments shall have sprayed in bed liner applied. Spray in Bed liner shall be applied to the bottom of the open area as well as the sides up to the top of the compartments. Vendor shall also spray the tops of the compartments with the same Material as the sides and bottom of the center opening of the bottom. There shall be four (4) drain holes, one in each corner, each drain hole shall have an opening no less than 1/4" open area after body has been painted and sprayed with spray in liner to allow for the drainage of rain and wash water | _____ | _____ |
| 30. | There shall be four (4) drain holes, one in each corner, each drain hole shall have an opening no less than 3/4" open area after body has been painted and sprayed with spray in liner to allow for the drainage of rain and wash water. | _____ | _____ |
| 31. | Four corner warning lights - Four (4) corner LED lights with rear round or square light heads recessed into the rear of the utility body Whelen brand LED or Equal-all LED with 5-year warranty. Front four (4) Corner Warning Lights shall not be installed in headlight/tum signal/parking light fixture. Any vehicle delivered with the front four corner warning lights installed in the headlight/tum signal/parking light fixtures will be refused and only accepted once vendor replaces the light fixture with the new ones. | _____ | _____ |
| 32. | Chassis to be provided with crank down spare tire mount with tire. Vendor shall make sure that both items are accessible with the body bid by bidder. | _____ | _____ |



PROCUREMENT DEPARTMENT

Potential bidders are responsible to check this site for any **ADDENDUMS** that are issued. It is the responsibility of the **BIDDER** to check for, download, and include with their **BID RESPONSE** any and all **ADDENDUMS** that are issued for a specific **BID** published by the City of Mobile. Failure to download and include **ADDENDUMS** in your **BID RESPONSE** may cause your bid to be rejected.

This is a sealed bid. Any responses faxed or emailed will be rejected.

This is a sealed bid. Any response must be submitted in a sealed envelope with the bid number and bid opening date on the outside of the envelope.

Any response that arrives improperly marked or with no bid number and opening date on the outside of the delivery or express package and opened in error will be rejected and not considered.

It is the responsibility of the bidder to ensure that their bid response is delivered to and received in the Purchasing Department before the date and time of the bid opening.

Please read the Terms and Conditions.

All bids are F.O.B. destination unless otherwise stated.

Please sign your bid.

Package/Bid Delivery Address (Request First Delivery):
Purchasing Department
205 Government St., RM S408
Mobile, AL 36644